

Kanlux

KANLUX LCOB 8W/M 24V

The Kanlux LCOB 24V LED strip is a unique lighting solution. It has a very high luminous efficacy and a 3-year warranty. Its unique feature is that it shines all the way through - there are no brighter or darker areas on it, no visible points of light. The Kanlux LCOB strip emits uniform light regardless of the depth of the profile and the transparency of the diffuser. The 24V version of the strip allows longer pieces to be used with the connection of a single power supply. Two versions of the strip are available: with IP65 or IP00 protection rating.

- 3 years Warranty under the terms of the warranty statement, available on our website



24V



 24 DC	 0,5m = 4		 ≤ 6x MacAdam	 Ra 90		
 COB	 LED m 320	 ≥30000	 30000 [h]		 0,1m	 5÷25 [°C]
 360° Φ _{use}						



LCOB 8W/M 24 IP00-WW



IP



LCOB 8W/M 24 IP00-WW	90660	1m = 8	1m = 736	3000	00	5000	F
LCOB 8W/M 24 IP00-NW	90665	1m = 8	1m = 800	4000	00	5000	F
LCOB 8W/M 24 IP00-CW	90670	1m = 8	1m = 800	6500	00	5000	F
LCOB 8W/M 24 IP65-WW	90663	1m = 8	1m = 680	3000	65	5000	G
LCOB 8W/M 24 IP65-NW	90668	1m = 8	1m = 760	4000	65	5000	F
LCOB 8W/M 24 IP65-CW	90673	1m = 8	1m = 760	6500	65	5000	F
LCOBB 8W/M 24 IP00-WW	90661	1m = 8	1m = 736	3000	00	25000	F
LCOBB 8W/M 24 IP00-NW	90666	1m = 8	1m = 800	4000	00	25000	F
LCOBB 8W/M 24 IP00-CW	90671	1m = 8	1m = 800	6500	00	25000	F
LCOBB 8W/M 24 IP65-WW	90664	1m = 8	1m = 680	3000	65	25000	G
LCOBB 8W/M 24 IP65-NW	90669	1m = 8	1m = 760	4000	65	25000	F
LCOBB 8W/M 24 IP65-CW	90674	1m = 8	1m = 760	6500	65	25000	F
LCOBC 8W/M 24 IP00-WW	90662	1m = 8	1m = 736	3000	00	50000	F
LCOBC 8W/M 24 IP00-NW	90667	1m = 8	1m = 800	4000	00	50000	F
LCOBC 8W/M 24 IP00-CW	90672	1m = 8	1m = 800	6500	00	50000	F



LCOB 8W/M 24 IP00-WW



LCOB 8W/M 24 IP00-NW



LCOB 8W/M 24 IP00-CW



LCOB 8W/M 24 IP65-WW




LCOB 8W/M 24 IP65-NW



LCOB 8W/M 24 IP65-CW



LCOBB 8W/M 24 IP00-WW



LCOBB 8W/M 24 IP00-NW



LCOBB 8W/M 24 IP00-CW



LCOBB 8W/M 24 IP65-WW



LCOBB 8W/M 24 IP65-NW



LCOBB 8W/M 24 IP65-CW




LCOBC 8W/M 24 IP00-WW




LCOBC 8W/M 24 IP00-NW




LCOBC 8W/M 24 IP00-CW




LCOB 8W/M 24 IP00-WW




LCOB 8W/M 24 IP00-NW




LCOB 8W/M 24 IP00-CW




LCOB 8W/M 24 IP65-WW




LCOB 8W/M 24 IP65-NW




LCOB 8W/M 24 IP65-CW




LCOBB 8W/M 24 IP00-WW




LCOBB 8W/M 24 IP00-NW




LCOBB 8W/M 24 IP00-CW




LCOBB 8W/M 24 IP65-WW




LCOBB 8W/M 24 IP65-NW




LCOBB 8W/M 24 IP65-CW



LCOBC 8W/M 24 IP00-WW



LCOBC 8W/M 24 IP00-NW



LCOBC 8W/M 24 IP00-CW

Accessories

38472 CON P 8 LED band connector, CON P 8 (38472)



38470 CON P 8 CP LED band connector, CON P 8 CP (38470)



38471 CON P 8 CPC LED band connector, CON P 8 CPC (38471)



38473 CON P 8 L LED band connector, CON P 8 L (38473)



Date of issue: 04.08.2026, 14:18
We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.
Kanalux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com