

Kanlux



Kanlux LCOB LONG

Kanlux LCOB LONG LED strips are designed for long, uniform light lines without noticeable brightness loss at the ends. Thanks to a special stabilizing system, even 20-meter sections can be powered without compromising light quality, which is a significant challenge for traditional LED strips. Densely spaced diodes (480 LEDs/m) and COB technology ensure a uniform line of light with high efficacy (up to 690 lm/m) and excellent color rendering (CRI 90). The strips are available in three light colors: warm 3000K, neutral 4000K, and cool 6500K, allowing them to be adapted to various spaces and needs. Flexible installation, cutting every 50mm, 20m rolls, and 24V voltage make Kanlux LCOB LONG the ideal solution for long, aesthetically pleasing, and trouble-free linear installations.

- 3 years Warranty under the terms of the warranty statement, available on our website



24V



 24 DC		 ≤ 60 Macadam	 Ra 90			 COB
 LED m 480	 ≥ 30000	 30000 [h]		 0,1m	 5÷25	



LCOBL 7,5W/M24IP00-WW



IP



LCOBL 7.5W/M24IP00-WW	38917	1m = 7,5	1m = 640	3000	00	20000	G
LCOBL 7.5W/M24IP00-NW	38918	1m = 7,5	1m = 690	4000	00	20000	F
LCOBL 7.5W/M24IP00-CW	38919	1m = 7,5	1m = 690	6500	00	20000	F




LCOBL 7,5W/M24IP00-WW




LCOBL 7,5W/M24IP00-NW




LCOBL 7,5W/M24IP00-CW



LCOBL 7,5W/M24IP00-WW



LCOBL 7,5W/M24IP00-NW



LCOBL 7,5W/M24IP00-CW

Accessories

38472 CON P 8 LED band connector, CON P 8 (38472)



38470 CON P 8 CP LED band connector, CON P 8 CP (38470)



38471 CON P 8 CPC LED band connector, CON P 8 CPC (38471)



38473 CON P 8 L LED band connector, CON P 8 L (38473)



Date of issue: 03.07.2026, 12:01
We reserve the right to make technical changes. The data contained in this material are not legally binding.
Photometry: the results obtained from testing were from a specific sample.
Kanalux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com