

KMB6

Protecteur de surtensions, 3P



[Hz] 50	B	3P	3	IP 20	1÷25 [mm²]	5÷40 [°C]
TH 35	Ui [V] 500	CE	EAC	VDE	UK CA	(V)

KMB6-B16/3

	[V]		In [A]
KMB6-B16/3	23149	230/400 AC	3 16
KMB6-B20/3	23152	230/400 AC	3 20
KMB6-B25/3	23153	230/400 AC	3 25
KMB6-B32/3	23159	230/400 AC	3 32
KMB6-B10/3	23164	230/400 AC	3 10
KMB6-B40/3	23168	230/400 AC	3 40
KMB6-B63/3	23170	230/400 AC	3 63
KMB6-B6/3	23171	230/400 AC	3 6
KMB6-B50/3	23172	230/400 AC	3 50

Le disjoncteur avec protection contre les surintensités est utilisé pour la protection des câbles contre les surcharges et les courts-circuits dans les installations et les appareils.

KMB6

Protecteur de surtensions, 3P



KMB6-B16/3



KMB6-B20/3



KMB6-B25/3



KMB6-B32/3



KMB6-B10/3



KMB6-B40/3




KMB6-B63/3




KMB6-B6/3




KMB6-B50/3




KMB6-B16/3



KMB6-B20/3




KMB6-B25/3




KMB6-B32/3

KMB6


Protecteur de surtensions, 3P




KMB6-B10/3




KMB6-B40/3



KMB6-B63/3



KMB6-B6/3



KMB6-B50/3