

## KIENO LED P1

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[L] ≥30000	[h] 50000	[+/-] ellipse ≤ 6x MacAdam	[Ra] 80	[SMD]
[ $\Omega$ ] 1,5÷2,5	[ $\oplus$ ] 0,5m	[IP] 20	[ $\square$ ]	[ $\text{K}$ ] 5÷25	[ $\text{W}$ ]	[ $\text{UKCA}$ ]



KN-M6D-NW-B-P1



KN-M6D-NW-B-P1	<b>37460</b>	37	4750	4000	soczewka	60	noir
KN-M6D-NW-W-P1	<b>37448</b>	37	5450	4000	soczewka	60	blanc
KN-M6D-WW-B-P1	<b>37454</b>	37	4450	3000	soczewka	60	noir
KN-M6D-WW-W-P1	<b>37442</b>	37	5100	3000	soczewka	60	blanc
KN-M9D-NW-B-P1	<b>37463</b>	37	4700	4000	soczewka	90	noir
KN-M9D-NW-W-P1	<b>37451</b>	37	5350	4000	soczewka	90	blanc
KN-M9D-WW-B-P1	<b>37457</b>	37	4350	3000	soczewka	90	noir
KN-M9D-WW-W-P1	<b>37445</b>	37	5000	3000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

## KIENO LED P1


Luminaire LED encastré pour bureau



KN-W-P1



KN-B-P1



KN-P1

