

KIENO LED P1

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[\geq 30000] 50000	[h] 50000	[Ra] ≤ 6x MacAdam	[Ra] 80	[SMD]
[mm^2] 1,5÷2,5	[D] 0,5m	[IP] 20	[W] 19	[Ra] 5÷25	[Ra] 80	[Ra] 80
		[CE]	[UKCA]			



KN-S6D-NW-B-P1

KN-S6D-NW-B-P1	37458	19	2650	4000	soczewka	60	noir	
KN-S6D-NW-W-P1	37446	19	3000	4000	soczewka	60	blanc	
KN-S6D-WW-B-P1	37452	19	2450	3000	soczewka	60	noir	
KN-S6D-WW-W-P1	37440	19	2800	3000	soczewka	60	blanc	
KN-S9D-NW-B-P1	37461	19	2600	4000	soczewka	90	noir	
KN-S9D-NW-W-P1	37449	19	2950	4000	soczewka	90	blanc	
KN-S9D-WW-B-P1	37455	19	2400	3000	soczewka	90	noir	
KN-S9D-WW-W-P1	37443	19	2750	3000	soczewka	90	blanc	

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

KIENO LED P1


Luminaire LED encastré pour bureau



KN-B-P1



KN-W-P1



KN-P1

