

# KIENO DALI LED P1


Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[h] ≥30000	[h] 50000	ellipse ≤ 6x MacAdam	Ra 80	SMD
DALI	IP 20	House	50000	5-25 °C	80	SMD
0,5-2,5 [mm <sup>2</sup> ]	0,5m	CE	UK CA			



KND-M6D-NW-B-P1



KND-M6D-NW-B-P1	<b>37484</b>	38	4750	4000	soczewka	60	noir
KND-M6D-NW-W-P1	<b>37472</b>	38	5450	4000	soczewka	60	blanc
KND-M6D-WW-B-P1	<b>37478</b>	38	4450	3000	soczewka	60	noir
KND-M6D-WW-W-P1	<b>37466</b>	38	5100	3000	soczewka	60	blanc
KND-M9D-NW-B-P1	<b>37487</b>	38	4700	4000	soczewka	90	noir
KND-M9D-NW-W-P1	<b>37475</b>	38	5350	4000	soczewka	90	blanc
KND-M9D-WW-B-P1	<b>37481</b>	38	4350	3000	soczewka	90	noir
KND-M9D-WW-W-P1	<b>37469</b>	38	5000	3000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

# KIENO DALI LED P1


Luminaire LED encastré pour bureau



KND B P1



KND W P1



KND P1

