

KIENO DALI LED P1

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[h] ≥30000	[h] 50000	ellipse ≤ 6x MacAdam	Ra 80	SMD
DALI	IP 20	House	50000	5-25 °C	80	SMD
[mm ²] 0,5-2,5	0,5m	CE	UK CA			



KND-S6D-NW-B-P1



KND-S6D-NW-B-P1	37482	20	2650	4000	soczewka	60	noir
KND-S6D-NW-W-P1	37470	20	3000	4000	soczewka	60	blanc
KND-S6D-WW-B-P1	37476	20	2450	3000	soczewka	60	noir
KND-S6D-WW-W-P1	37464	20	2800	3000	soczewka	60	blanc
KND-S9D-NW-B-P1	37485	20	2600	4000	soczewka	90	noir
KND-S9D-NW-W-P1	37473	20	2950	4000	soczewka	90	blanc
KND-S9D-WW-B-P1	37479	20	2400	3000	soczewka	90	noir
KND-S9D-WW-W-P1	37467	20	2750	3000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

KIENO DALI LED P1


Luminaire LED encastré pour bureau



KND B P1



KND W P1



KND P1

