

KIENO DALI LED P1

Luminaire LED encastré pour bureau



| | | | | | | |
|-------------------|------------|-----------------|--------------|----------------------------------|------------|-----|
| [V] 220-240 AC | [Hz] 50 | [min] ≥30000 | [h] 50000 | [+/-] ellipse ≤ 6x MacAdam | [Ra] 80 | SMD |
| DALI | + | IP 20 | House | 5-25 [°C] | Up/Down | Box |
| [mm²] 0,5-2,5 | 0,5m | CE | UK CA | | | |



KND-L6D-NW-B-P1



| | | | | | | | |
|-----------------|--------------|----|------|------|----------|----|-------|
| KND-L6D-NW-B-P1 | 37483 | 26 | 3600 | 4000 | soczewka | 60 | noir |
| KND-L6D-NW-W-P1 | 37471 | 26 | 4100 | 4000 | soczewka | 60 | blanc |
| KND-L6D-WW-B-P1 | 37477 | 26 | 3350 | 3000 | soczewka | 60 | noir |
| KND-L6D-WW-W-P1 | 37465 | 26 | 3850 | 3000 | soczewka | 60 | blanc |
| KND-L9D-NW-B-P1 | 37486 | 26 | 3550 | 4000 | soczewka | 90 | noir |
| KND-L9D-NW-W-P1 | 37474 | 26 | 4050 | 4000 | soczewka | 90 | blanc |
| KND-L9D-WW-B-P1 | 37480 | 26 | 3350 | 3000 | soczewka | 90 | noir |
| KND-L9D-WW-W-P1 | 37468 | 26 | 3800 | 3000 | soczewka | 90 | blanc |

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

KIENO DALI LED P1


Luminaire LED encastré pour bureau



KN-B-P1



KN-W-P1



KN-P1

