

KIENO LED P3

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[L] ≥ 30000	[h] 50000	[Ra] $\leq 6x$ MacAdam	[Ra] 80	SMD
[mm^2] 1,5÷2,5	D---m 0,5m	IP 20	[House]	[Thermometer] 5÷25	[Up/Down]	[Box]
CE	UK CA					



KN-M6D-NW-B-P3



KN-M6D-NW-B-P3	37508	35	5250	4000	soczewka	60	noir
KN-M6D-NW-W-P3	37496	35	6000	4000	soczewka	60	blanc
KN-M6D-WW-B-P3	37502	35	4950	3000	soczewka	60	noir
KN-M6D-WW-W-P3	37490	35	5650	3000	soczewka	60	blanc
KN-M9D-NW-B-P3	37511	35	5100	4000	soczewka	90	noir
KN-M9D-NW-W-P3	37499	35	5100	4000	soczewka	90	blanc
KN-M9D-WW-B-P3	37505	35	4900	3000	soczewka	90	noir
KN-M9D-WW-W-P3	37493	35	5500	3000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

KIENO LED P3


Luminaire LED encastré pour bureau



KN-B-P3



KN-W-P3



KN-P3

