

KIENO LED P3

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[L] ≥30000	[h] 50000	[Ra] ≤6x MacAdam	[Ra] 80	[SMD]
[Ω]	[\oplus]	[IP] 20	[\square]	[\star] 5÷25	[\star]	[\square]
[mm^2] 1,5÷2,5	[m] 0,5m	[CE]	[UKCA]			



KN-S6D-NW-B-P3



KN-S6D-NW-B-P3	37506	18	2750	4000	soczewka	60	noir
KN-S6D-NW-W-P3	37494	18	3150	4000	soczewka	60	blanc
KN-S6D-WW-B-P3	37500	18	2600	3000	soczewka	60	noir
KN-S6D-WW-W-P3	37488	18	2950	3000	soczewka	60	blanc
KN-S9D-NW-B-P3	37509	18	2650	4000	soczewka	90	noir
KN-S9D-NW-W-P3	37497	18	2650	4000	soczewka	90	blanc
KN-S9D-WW-B-P3	37503	18	2550	3000	soczewka	90	noir
KN-S9D-WW-W-P3	37491	18	2850	3000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

KIENO LED P3


Luminaire LED encastré pour bureau



KN-B-P3



KN-W-P3



KN-P3

