

KIENO LED P3

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[Hz] ≥30000	[h] 50000	[Ra] ≤6x MacAdam	[Ra] 80	[SMD]
[W] 1,5÷2,5	[mA] 0,5m	[IP] 20	[House]	[Thermometer] 5÷25	[Up/Down]	[Box]
		[CE]	[UK CA]			



KN-L6D-NW-B-P3



KN-L6D-NW-B-P3	37507	25	3850	4000	soczewka	60	noir
KN-L6D-NW-W-P3	37495	25	4400	4000	soczewka	60	blanc
KN-L6D-WW-B-P3	37501	25	3650	3000	soczewka	60	noir
KN-L6D-WW-W-P3	37489	25	4150	3000	soczewka	60	blanc
KN-L9D-NW-B-P3	37510	25	3750	4000	soczewka	90	noir
KN-L9D-NW-W-P3	37498	25	3750	4000	soczewka	90	blanc
KN-L9D-WW-B-P3	37504	25	3600	3000	soczewka	90	noir
KN-L9D-WW-W-P3	37492	25	4050	3000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

KIENO LED P3


Luminaire LED encastré pour bureau



KN-B-P3



KN-W-P3



KN-P3

