

## KIENO DALI LED P3

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[L] $\geq 30000$	[h] 50000	[ $\Delta E_{uv}$ ] ellipse $\leq 6x$ MacAdam	[Ra] 80	[SMD]
[DALI]	[ $\oplus$ ]	[IP] 20	[House]	[Thermometer] 5÷25	[Up/Down]	[Box]
[ $\text{mm}^2$ ] 0,5÷2,5	[D] 0,5m	[CE]	[UK CA]			



KND-S6D-NW-B-P3

		[W]	[lm]	T <sub>c</sub> [K]	TYPE	[°]	
KND-S6D-NW-B-P3	<b>37530</b>	19	2750	4000	soczewka	60	noir
KND-S6D-NW-W-P3	<b>37518</b>	19	3150	4000	soczewka	60	blanc
KND-S6D-WW-B-P3	<b>37524</b>	19	2600	3000	soczewka	60	noir
KND-S6D-WW-W-P3	<b>37512</b>	19	2950	3000	soczewka	60	blanc
KND-S9D-NW-B-P3	<b>37533</b>	19	2650	4000	soczewka	90	noir
KND-S9D-NW-W-P3	<b>37521</b>	18	2650	4000	soczewka	90	blanc
KND-S9D-WW-B-P3	<b>37527</b>	19	2550	3000	soczewka	90	noir
KND-S9D-WW-W-P3	<b>37515</b>	19	2850	3000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

## KIENO DALI LED P3


Luminaire LED encastré pour bureau



KND-B-P3



KND-W-P3



KND-P3

