

KIENO DALI LED P3

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[s] ≥30000	[h] 50000	[+/-] ellipse ≤ 6x MacAdam	[Ra] 80	[SMD]
[DALI]	[IP] 20	[House]	[Thermometer] 5÷25	[Up/Down]	[UKCA]	[Box]
[mm ²] 0,5÷2,5	[D---m] 0,5m	[CE]				



KND-L6D-NW-B-P3



KND-L6D-NW-B-P3	37531	26	3850	4000	soczewka	60	noir
KND-L6D-NW-W-P3	37519	26	4400	4000	soczewka	60	blanc
KND-L6D-WW-B-P3	37525	26	3650	3000	soczewka	60	noir
KND-L6D-WW-W-P3	37513	26	4150	3000	soczewka	60	blanc
KND-L9D-NW-B-P3	37534	26	3750	4000	soczewka	90	noir
KND-L9D-NW-W-P3	37522	25	3750	4000	soczewka	90	blanc
KND-L9D-WW-B-P3	37528	26	3600	3000	soczewka	90	noir
KND-L9D-WW-W-P3	37516	26	4050	3000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

KIENO DALI LED P3


Luminaire LED encastré pour bureau



KND-B-P3



KND-W-P3



KND-P3

