

KIENO LED P1D

Luminaire LED encastré pour bureau



low
UGR

[V] 220-240 AC	[Hz] 50	[\geq 30000]	[h] 50000	[Ra] $\leq 6x$ MacAdam	[Ra] 80	SMD
[W] 1,5÷2,5	[lm] 0,5m	IP 20	[m^2] 0,5m	CE	UK CA	



KNU-L6D-NW-B-P1D

		[W]	[lm]	T _c [K]	TYPE	[°]	
KNU-L6D-NW-B-P1D	37546	25	3850	4000	soczewka	60	noir
KNU-L6D-NW-W-P1D	37540	25	4400	4000	soczewka	60	blanc
KNU-L6D-WW-B-P1D	37543	25	3650	3000	soczewka	60	noir
KNU-L6D-WW-W-P1D	37537	25	4150	3000	soczewka	60	blanc
KNU-L9D-NW-W-P1D	38237	25	4400	4000	soczewka	90	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

KIENO LED P1D

Luminaire LED encastré pour bureau




KNU-B-P1D




KNU-W-P1D



KNU-L9D-NW-W-P1D



KNU-P1D



KNU-L9D-NW-W-P1D

