

## KIENO DALI LED P1D

Luminaire LED encastré pour bureau



[V] 220-240 AC	[Hz] 50	[L] ≥30000	[h] 50000	[+/-] ≤ 6x MacAdam	[Ra] 80	[SMD]
[DALI]	[ $\oplus$ ]	[IP] 20	[House]	[ $\Delta$ ] 5-25	[ $\Delta$ ]	[ $\Delta$ ]
[ $\Delta$ mm <sup>2</sup> ] 0,5-2,5	[D---m] 0,5m	[CE]	[UK CA]			



KNDU-L6D-NW-B-P1D

		[W]	[lm]	Tc [K]	TYPE	[°]	
KNDU-L6D-NW-B-P1D	<b>37558</b>	26	3850	4000	soczewka	60	noir
KNDU-L6D-NW-W-P1D	<b>37552</b>	26	4400	4000	soczewka	60	blanc
KNDU-L6D-WW-B-P1D	<b>37555</b>	26	3650	3000	soczewka	60	noir
KNDU-L6D-WW-W-P1D	<b>37549</b>	26	4150	3000	soczewka	60	blanc

- Matériau du boîtier: métal
- Matériau du diffuseur: matériau plastique

## KIENO DALI LED P1D


Luminaire LED encastré pour bureau



KNDU-B-P1D



KNDU-W-P1D



KNDU-P1D

