

Disjoncteur différentiel, 2P



[Hz]

50

°C

-25÷40

IP

20

2P

2

TH 35

Ui [V]

400

mm²

max 25

CE

EAC

VDE

UK
CA

Recycling symbol

KRD10-2/16/30-F

	[V]	In [A]	IΔn [mA]	Type de protection contre les courants résiduels		
KRD10-2/16/30-F	45769	230 AC 16	30	F		2
KRD10-2/25/30-F	45770	230 AC 25	30	F		2
KRD10-2/40/30-F	45771	230 AC 40	30	F		2
KRD10-2/25/100-F	45772	230 AC 25	100	F		2
KRD10-2/40/100-F	45773	230 AC 40	100	F		2
KRD10-2/25/300-F	45774	230 AC 25	300	F		2
KRD10-2/40/300-F	45775	230 AC 40	300	F		2

Disjoncteur différentiel, 2P



KRD10-2/16/30-F



KRD10-2/25/30-F



KRD10-2/40/30-F



KRD10-2/25/100-F




KRD10-2/40/100-F




KRD10-2/25/300-F




KRD10-2/40/300-F




KRD10-2/16/30-F



KRD10-2/25/30-F




KRD10-2/40/30-F




KRD10-2/25/100-F


Disjoncteur différentiel, 2P



KRD10-2/40/100-F



KRD10-2/25/300-F



KRD10-2/40/300-F