



[V] 220-240 AC	[Hz] 50	[h] ≥30000	[h] 50000	ellipse ≤3x Macdonald	Ra 80	SMD
		IP 65		IK 08		
[mm] 1,5÷2,5	[m] 0,5m					



FT1500 55W-840-RYF

		[W]	Tc [K]	TYPE	[°]	[lm]	W	[mm]	[°C]
FT1500 55W-840-RYF	28659	55	4000	barázdált	X115/Y105	8150	148	1480	-25÷35
FT1500 55W-840-INT	28661	55	4000	prizmás, keskenysugaras	X70/Y95	7900	144	1480	-25÷35
FT1500 55W-840-ASY	28662	55	4000	prizmás, aszimmetrikus	X75/Y95	7900	144	1480	-25÷35
FT1500 55W-840-OPL	28665	55	4000	opál	X130/Y110	7500	136	1480	-25÷35



FT1500 55W-840-RYF




FT1500 55W-840-INT




FT1500 55W-840-ASY




FT1500 55W-840-OPL




FTI200 55W-840



FTI200 55W-840



FTI200 55W-840



FTI200 55W-840

Létrehozás dátuma: 28.07.2025, 20:10

Fenntartjuk a műszaki változtatások bevezetésének jogát. A jelen anyagban található adatok jogi szempontból nem kötelező érvényűek.

Fotometria: adott termék vizsgálatkor elért eredmények.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

