



DALI
system

 [V] 220-240 AC	 [Hz] 50	 ≥30000	 50000	 elliptical ≤3x Macdonald	 Ra 80	 SMD
 DALI	 —	 IP 65		 IK 08		
 [mm] 0,5÷2,5	 0,5m	 CE	 EAC	 PZH	 UK CA	



FTD1200 28W-840-OPL

		 [W]	 Tc [K]	 TYPE	 [°]	 [lm]	 lm W	 [mm]	 [°C]
FTD1200 28W-840-OPL	28854	28	4000	opál	X130/Y110	4100	146	1180	-25÷40
FTD1200 28W-840-RYF	28855	28	4000	barázdált	X115/Y105	4500	161	1180	-25÷40
FTD1200 28W-840-INT	28856	28	4000	prizmás, keskenysugaras	X70/Y95	4300	154	1180	-25÷40
FTD1200 28W-840-ASY	28857	28	4000	prizmás, aszimmetrikus	X75/Y95	4300	154	1180	-25÷40



FTD1200 28W-840-OPL




FTD1200 28W-840-RYF




FTD1200 28W-840-INT




FTD1200 28W-840-ASY




FTD1200 28W-840-OPL



FTD1200 28W-840-RYF



FTD1200 28W-840-INT



FTD1200 28W-840-ASY

Létrehozás dátuma: 28.07.2025, 20:10

Fenntartjuk a műszaki változtatások bevezetésének jogát. A jelen anyagban található adatok jogi szempontból nem kötelező érvényűek.

Fotometria: adott termék vizsgálatakor elért eredmények.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

