

FUTURIO LED DALI 55W 1480mm

Plafoniera stagna led



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65			IK 08	
[mm ²] 0,5+2,5	[m] 0,5m	CE	EAC	PZH	UK CA	



FTD1500 55W-840-OPL

	[V]	Tc [K]	TYPE	[°]	[lm]	lm W	[mm]	[°C]	
FTD1500 55W-840-OPL	28658	55	4000	opalescente	X130/Y110	7500	136	1480	-25÷35
FTD1500 55W-840-RYF	28666	55	4000	grooved	X115/Y105	8150	148	1480	-25÷35
FTD1500 55W-840-INT	28668	55	4000	prismatico, a fascio stretto	X70/Y95	7900	144	1480	-25÷35
FTD1500 55W-840-ASY	28669	55	4000	prismatico, asimmetrico	X75/Y95	7900	144	1480	-25÷35

- 5 anni di garanzia secondo le condizioni della dichiarazione di garanzia consultabile sul sito Internet
- Materiale del corpo: PC
- Materiale del diffusore: PC



FTD1500 55W-840-OPL



FTD1500 55W-840-RYF




FTD1500 55W-840-INT




FTD1500 55W-840-ASY

FUTURIO LED DALI 55W 1480mm


Plafoniera stagna led




FTD1500 55W-840-OPL



FTD1500 55W-840-RYF



FTD1500 55W-840-INT



FTD1500 55W-840-ASY