

## XLED C35M

Lampadina led



[V] 220-240 AC	[Hz] 50	FILAMENT	360° Φ <sub>use</sub>	ellipse ≤ 6x Macadam	Ra 80	≥15000
		CE	EAC	UK CA		



XLED C35E14 4,5W-WW-M



	PON [W]	[W]	[lm] Φ <sub>use</sub>	Tc [K]	[°]	filament	[h]	E <sub>i</sub> A/G	
XLED C35E14 4,5W-WW-M	29620	4,5	40	470	2700	320	E14	15000	F
XLED C35E14 4,5W-NW-M	29621	4,5	40	470	4000	320	E14	15000	F
XLED C35E14 6W-WW-M	29622	6	60	810	2700	320	E14	10000	D
XLED C35E14 6W-NW-M	29623	6	60	810	4000	320	E14	10000	D
XLED C35E27 6W-WW-M	29646	6	60	810	2700	320	E27	10000	D
XLED C35E27 6W-NW-M	29647	6	60	810	4000	320	E27	10000	D

Kanlux XLED combina le migliori caratteristiche delle lampade tradizionali con le più moderne lampadine LED. Inoltre siamo soliti riferirci a questo tipo di lampada come la prima vera lampada LED. La versione opaca con la classica forma di candela diffonde la luce in modo ampio e uniforme raggiungendo i 320° di rifrazione.

- Diffusore: vetro

## XLED C35M


Lampadina led




XLED C35E14 4,5W, XLED  
C35E14 6W



XLED C35E27 6W



XLED C35E14 4,5W, XLED  
C35E14 6W



XLED C35E27 6W