

# KMB6

Interruttori automatici, 2P



[Hz]  
50

B

2P

2

IP

20

[mm²]  
1÷25

°C  
5÷40

TH 35

Ui [V]

500

VDE

UK

CA

KMB6-B6/2

	<div>[V]</div>	<div></div>	<div>In [A]</div>
KMB6-B6/2	<b>32574</b> 230 AC	2	6
KMB6-B10/2	<b>32575</b> 230 AC	2	10
KMB6-B16/2	<b>32576</b> 230 AC	2	16
KMB6-B20/2	<b>32577</b> 230 AC	2	20
KMB6-B25/2	<b>32578</b> 230 AC	2	25
KMB6-B32/2	<b>32579</b> 230 AC	2	32
KMB6-B40/2	<b>32580</b> 230 AC	2	40
KMB6-B50/2	<b>32581</b> 230 AC	2	50
KMB6-B63/2	<b>32582</b> 230 AC	2	63

Interruttore automatico magnetotermico:utilizzato per la protezione da sovraccarichi e cortocircuiti.  
Conforme alle norme EN60898-1.

## KMB6

Interruttori automatici, 2P



KMB6-B6/2



KMB6-B10/2



KMB6-B16/2



KMB6-B20/2



KMB6-B25/2



KMB6-B32/2




KMB6-B40/2




KMB6-B50/2




KMB6-B63/2




KMB6-B6/2



KMB6-B10/2




KMB6-B16/2




KMB6-B20/2

## KMB6


Interruttori automatici, 2P




KMB6-B25/2




KMB6-B32/2



KMB6-B40/2



KMB6-B50/2



KMB6-B63/2