

KP-DB-I-MF M

Quadro di distribuzione in metallo



KP-DB-I-MF-312M

[V]

230/400 AC

[Hz]

50

In[A]

63



			IP	 MATERIAL
KP-DB-I-MF-312M	46431	bianco	30	metallo
KP-DB-I-MF-318M	46436	bianco	30	metallo
KP-DB-I-MF-418M	46437	bianco	30	metallo
KP-DB-I-MF-518M	46438	bianco	30	metallo



KP-DB-I-MF-312M



KP-DB-I-MF-318M




KP-DB-I-MF-418M



KP-DB-I-MF-518M

KP-DB-I-MF M

Quadro di distribuzione in metallo



SYMBOL	A	B	C
KP-DB-I-MF-312M	375	581	115
KP-DB-I-MF-318M	485	578	115
KP-DB-I-MF-418M	485	711	115
KP-DB-I-MF-518M	485	849	115

Data di emissione: 13.08.2026, 09:08

Ci riserviamo la possibilità di introdurre delle modifiche tecniche. I dati contenuti in questo materiale non sono legalmente vincolanti.

Fotometria: risultati conseguiti durante l'esame di una singola unità del prodotto.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com