



## ALIN 4LED 630mm NT

Oprawa liniowa pod tuby LED T8



<b>[V]</b> 220-240 AC	<b>[Hz]</b> 50	<b>[W]</b> max 18	<b>G13</b>	<b>IP</b> 20	
<b>[°C]</b> 5÷25			<b>[mm<sup>2</sup>]</b> 1,5+2,5	<b>L N</b> ONE SIDE INPUT	 <b>0,5m</b>
<b>CE</b>	<b>EAC</b>	<b>PZH</b>	<b>UK</b> <b>CA</b>		



### ALIN 4LED 1X60-W-NT

		<b>TYPE</b> 			<b>[mm]</b> 
ALIN 4LED 1X60-W-NT	<b>27416</b>	matowy	biały	T8 LED	630
ALIN 4LED 1X60-SR-NT	<b>27418</b>	matowy	srebrny	T8 LED	630
ALIN 4LED 1X60-B-NT	<b>27417</b>	matowy	czarny	T8 LED	630
AL 4LED 60-MPR-W-NT	<b>28440</b>	mikropryzmatyczny	biały	T8 LED	630
AL 4LED 60-MPR-SR-NT	<b>28442</b>	mikropryzmatyczny	srebrny	T8 LED	630
AL 4LED 60-MPR-B-NT	<b>28441</b>	mikropryzmatyczny	czarny	T8 LED	630

- Atest PZH: Numer BK/K/0927/01/2018, ważny do 2023-11-28
- Materiał obudowy: stop aluminium
- Materiał klosza: tworzywo sztuczne

## ALIN 4LED 630mm NT

Oprawa liniowa pod tuby LED T8



ALIN 4LED 1X60-W-NT



ALIN 4LED 1X60-SR-NT



ALIN 4LED 1X60-B-NT



AL 4LED 60-MPR-W-NT



AL 4LED 60-MPR-SR-NT




AL 4LED 60-MPR-B-NT


## ALIN 4LED 630mm NT

---

Oprawa liniowa pod tuby LED T8



ALIN 4LED 1X60



ALIN 4LED 60-MPR