

FUTURIO LED 37W 1180mm

Oprawa pyłoszczelna LED



[V] 220-240 AC	[Hz] 50	≥ 30000	[h] 50000	$\leq 3x$ MacAdam	Ra 80	SMD
		IP 65			IK 08	
[mm ²] 1,5÷2,5	0,5m	CE	EAC	PZH	UK CA	



FT1200 37W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[mm]	lm	[mm]	[°C]	
FT1200 37W-840-OPL	28630	37	4000	opalowy	X130/Y110	5000	135	1180	-25÷40
FT1200 37W-840-RYF	28631	37	4000	ryflowany	X115/Y105	5400	146	1180	-25÷40
FT1200 37W-840-INT	28633	37	4000	pryzmatyczny, wąskostrumieniowy	X70/Y95	5200	141	1180	-25÷40
FT1200 37W-840-ASY	28634	37	4000	pryzmatyczny, asymetryczny	X75/Y95	5200	141	1180	-25÷40

- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Atest PZH: Numer BK/K/0163/01/2019, ważny do 2024-08-07
- Materiał obudowy: PC
- Materiał klosza: PC

FUTURIO LED 37W 1180mm

Oprawa pyłoszczelna LED



FT1200 37W-840-OPL




FT1200 37W-840-RYF




FT1200 37W-840-INT




FT1200 37W-840-ASY




FT1200 37W-840-OPL



FT1200 37W-840-RYF



FT1200 37W-840-INT



FT1200 37W-840-ASY