

## FUTURIO LED DALI 55W 1480mm

Oprawa pyłoszczelna LED



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65			IK 08	
[mm] 0,5+2,5	0,5m	CE	EAC	PZH	UK CA	



### FTD1500 55W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[lm]	lm/W	[mm]	[°C]	
FTD1500 55W-840-OPL	<b>28658</b>	55	4000	opalowy	X130/Y110	7500	136	1480	-25÷35
FTD1500 55W-840-RYF	<b>28666</b>	55	4000	ryflowany	X115/Y105	8150	148	1480	-25÷35
FTD1500 55W-840-INT	<b>28668</b>	55	4000	pryzmatyczny, wąskostrumieniowy	X70/Y95	7900	144	1480	-25÷35
FTD1500 55W-840-ASY	<b>28669</b>	55	4000	pryzmatyczny, asymetryczny	X75/Y95	7900	144	1480	-25÷35

- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Atest PZH: Numer BK/K/0163/01/2019, ważny do 2024-08-07
- Materiał obudowy: PC
- Materiał klosza: PC



FTD1500 55W-840-OPL



FTD1500 55W-840-RYF




FTD1500 55W-840-INT




FTD1500 55W-840-ASY

## FUTURIO LED DALI 55W 1480mm


Oprawa pyłoszczelna LED




FTD1500 55W-840-OPL



FTD1500 55W-840-RYF



FTD1500 55W-840-INT



FTD1500 55W-840-ASY