

FUTURIO LED 55W 1480mm

Oprawa pyłoszczelna LED



| | | | | | | |
|-------------------------------|------------|-----------------|--------------|------------------------------|------------------------|-----|
| [V] 220-240 AC | [Hz] 50 | ≥ 30000 | [h] 50000 | ellipse $\leq 3x$ MacAdam | Ra 80 | SMD |
| | | IP 65 | | | IK 08 | |
| [mm ²] 1,5÷2,5 | 0,5m | CE | EAC | PZH | UK CA | |



FT1500 55W-840-RYF

| | [W] | Tc [K] | TYPE | [°] | [lm] | lm | [mm] | [°C] | |
|--------------------|--------------|--------|------|---------------------------------|-----------|------|------|------|--------|
| FT1500 55W-840-RYF | 28659 | 55 | 4000 | ryflowany | X115/Y105 | 8150 | 148 | 1480 | -25÷35 |
| FT1500 55W-840-INT | 28661 | 55 | 4000 | pryzmatyczny, wąskostrumieniowy | X70/Y95 | 7900 | 144 | 1480 | -25÷35 |
| FT1500 55W-840-ASY | 28662 | 55 | 4000 | pryzmatyczny, asymetryczny | X75/Y95 | 7900 | 144 | 1480 | -25÷35 |
| FT1500 55W-840-OPL | 28665 | 55 | 4000 | opalowy | X130/Y110 | 7500 | 136 | 1480 | -25÷35 |

- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Atest PZH: Numer BK/K/0163/01/2019, ważny do 2024-08-07
- Materiał obudowy: PC
- Materiał klosza: PC

FUTURIO LED 55W 1480mm

Oprawa pyłoszczelna LED



FT1500 55W-840-RYF




FT1500 55W-840-INT




FT1500 55W-840-ASY




FT1500 55W-840-OPL




FT1200 55W-840



FT1200 55W-840



FT1200 55W-840



FT1200 55W-840