

FUTURIO LED DALI 55W 1480mm

Oprawa płytuszczelna LED



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65		IK 08		
[mm²] 0,5÷2,5	0,5m					



FTD1500 55W-840-OPL

	[W]	[mm]	[mm]	TYPE	[°]	[lm]	[W]	[mm]	[°C]
FTD1500 55W-840-OPL	28658	55	4000	opalowy	X130/Y110	7500	136	1480	-25÷35
FTD1500 55W-840-RYF	28666	55	4000	ryflowany	X115/Y105	8150	148	1480	-25÷35
FTD1500 55W-840-INT	28668	55	4000	pryzmatyczny, wąskostrumieniowy	X70/Y95	7900	144	1480	-25÷35
FTD1500 55W-840-ASY	28669	55	4000	pryzmatyczny, asymetryczny	X75/Y95	7900	144	1480	-25÷35

- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Atest PZH: Numer BK/K/0163/01/2019, ważny do 2024-08-07
- Materiał obudowy: PC
- Materiał klosza: PC

FUTURIO LED DALI 55W 1480mm

Oprawa pyłoszczelna LED



FTD1500 55W-840-OPL




FTD1500 55W-840-RYF




FTD1500 55W-840-INT




FTD1500 55W-840-ASY




FTD1500 55W-840-OPL



FTD1500 55W-840-RYF



FTD1500 55W-840-INT



FTD1500 55W-840-ASY