

FUTURIO LED 28W 1180mm

Oprawa pyłoszczelna LED



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
		IP 65			IK 08	
[mm²] 1,5÷2,5	0,5m	CE	EAC	PZH	UK CA	



FT1200 28W-840-OPL

	[W]	Tc [K]		[mm]	[°C]
FT1200 28W-840-OPL	28850	28	4000	opalowy	X130/Y110 4100 146 1180 -25÷40
FT1200 28W-840-RYF	28851	28	4000	ryflowany	X115/Y105 4500 161 1180 -25÷40
FT1200 28W-840-INT	28852	28	4000	pryzmatyczny, wąskostrumieniowy	X70/Y95 4300 154 1180 -25÷40
FT1200 28W-840-ASY	28853	28	4000	pryzmatyczny, asymetryczny	X75/Y95 4300 154 1180 -25÷40

- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Atest PZH: Numer BK/K/0163/01/2019, ważny do 2024-08-07
- Materiał obudowy: PC
- Materiał klosza: PC

FUTURIO LED 28W 1180mm

Oprawa pyłoszczelna LED



FT1200 28W-840-OPL




FT1200 28W-840-RYF



FT1200 28W-840-INT



FT1200 28W-840-ASY



FT1200 28W-840