

## FUTURIO LED 43W 1480mm

Oprawa pyłoszczelna LED



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
		<b>IP</b> 65			<b>IK</b> 08	
[mm²] 1,5÷2,5	0,5m	<b>CE</b>	<b>EAC</b>	<b>PZH</b>	<b>UK</b> <b>CA</b>	



FT1500 43W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[mm]	[m]	[mm]	[°C]
FT1500 43W-840-OPL	<b>28858</b>	43	4000	opalowy	X130/Y110	6100	142	1480 -25÷40
FT1500 43W-840-RYF	<b>28859</b>	43	4000	ryflowany	X115/Y105	6500	151	1480 -25÷40
FT1500 43W-840-INT	<b>28860</b>	43	4000	pryzmatyczny, wąskostrumieniowy	X70/Y95	6300	147	1480 -25÷40
FT1500 43W-840-ASY	<b>28861</b>	43	4000	pryzmatyczny, asymetryczny	X75/Y95	6300	147	1480 -25÷40

- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Atest PZH: Numer BK/K/0163/01/2019, ważny do 2024-08-07
- Materiał obudowy: PC
- Materiał klosza: PC

## FUTURIO LED 43W 1480mm

### Oprawa pyłoszczelna LED



FT1500 43W-840-OPL




FT1500 43W-840-RYF




FT1500 43W-840-INT




FT1500 43W-840-ASY




FT1500 43W-840-OPL



FT1500 43W-840-RYF



FT1500 43W-840-INT



FT1500 43W-840-ASY