

FUTURIO LED 73W 1480mm

Oprawa płytuszczelna LED



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
DALI		IP 65		IK 08		
[mm²] 0,5÷2,5	0,5m	CE	EAC	UK CA		



FTHL1500 73W-840-OPL

	[W]	Tc [K]		TYPE	[°]	[mm]	lm W	[mm]	[°C]
FTHL1500 73W-840-OPL	28866	73	4000	opalowy	X130/Y110	9400	129	1480	-25÷35
FTHL1500 73W-840-RYF	28867	73	4000	ryflowany	X115/Y105	10200	140	1480	-25÷35
FTHL1500 73W-840-INT	28868	73	4000	pryzmatyczny, wąskostrumieniowy	X70/Y95	9800	134	1480	-25÷35
FTHL1500 73W-840-ASY	28869	73	4000	pryzmatyczny, asymetryczny	X75/Y95	9800	134	1480	-25÷35

- 5 lat Gwarancji na warunkach oświadczenia gwarancyjnego, dostępnego na stronie internetowej
- Attest PZH: Numer BK/K/0163/01/2019, ważny do 2024-08-07
- Materiał obudowy: PC
- Materiał klosza: PC

FUTURIO LED 73W 1480mm

Oprawa pyłoszczelna LED



FTHL1500 73W-840-OPL




FTHL1500 73W-840-RYF




FTHL1500 73W-840-INT




FTHL1500 73W-840-ASY




FTHL1500 73W-840-OPL



FTHL1500 73W-840-RYF



FTHL1500 73W-840-INT



FTHL1500 73W-840-ASY