

HIBO LED N

Oprawa LED high bay



 [V] 220-240 AC	 [Hz] 50	 [°] 120	 ≥20000	 [h] 25000	 ≤ 6x MacAdam	 Ra 80
 SMD			 IP 65		 -20÷40	
		 [m] 0,45	 [mm] 1		 1m	 120° Φ _{use}
						

HIBO LED N 50W-NW



HIBO LED N 50W-NW	31111	50	4750	4000	4000	czarny	F
HIBO LED N 100W-NW	31112	100	10000	8200	4000	czarny	F
HIBO LED N 150W-NW	31113	150	15000	12300	4000	czarny	F
HIBO LED N 200W-NW	31114	200	20000	16450	4000	czarny	F

HIBO LED to oprawa typu "High Bay" wykorzystująca moduł LED z diodami SMD. Oprawa posiada wysoki stopień szczelności IP65, dzięki czemu można ją zamontować w miejscach o wysokim zapyleniu i narażonych na działanie wody. Jest to oprawa przemysłowa, która doskonale sprawdzi się jako oświetlenie hal magazynowych, produkcyjnych oraz dużych przestrzeni handlowych.

- Materiał szyby ochronnej: szkło

HIBO LED N

Oprawa LED high bay



HIBO LED N 50W-NW




HIBO LED N 100W-NW




HIBO LED N 150W-NW




HIBO LED N 200W-NW




HIBO LED N 50W



HIBO LED N 100W



HIBO LED N 150W



HIBO LED N 200W