

KMB6

Wyłącznik nadmiarowo-prądowy, 1P+N



[Hz] 50	I _{cn} [A] 6000	C	1+N	IP 20	[mm ²] 1÷25	°C -5÷40
TH 35	U _i [V] 500					



KMBN6-C6/1

	[V]		I _n [A]
KMBN6-C6/1	32567	230/400 AC	1 6
KMBN6-C10/1	32568	230/400 AC	1 10
KMBN6-C16/1	32569	230/400 AC	1 16
KMBN6-C20/1	32570	230/400 AC	1 20
KMBN6-C25/1	32571	230/400 AC	1 25
KMBN6-C32/1	32572	230/400 AC	1 32

Wyłącznik z zabezpieczeniem nadmiarowo-prądowym służy do ochrony przewodów przed przeciążeniami i zwarciami w instalacjach i urządzeniach.

KMB6

Wyłącznik nadmiarowo-prądowy, 1P+N



KMBN6-C6/1



KMBN6-C10/1



KMBN6-C16/1




KMBN6-C20/1




KMBN6-C25/1




KMBN6-C32/1




KMBN6-C6/1



KMBN6-C10/1




KMBN6-C16/1




KMBN6-C20/1

KMB6

Wyłącznik nadmiarowo-prądowy, 1P+N



KMBN6-C25/1



KMBN6-C32/1