

Wyłącznik różnicowo-prądowy, 4P



[Hz] 50	°C -25÷40	IP 20	0000 4P	0 4	TH 35	Ui [V] 400
(mm²) max 25	CE	EAC	VDE	UK CA		

KRD10-4/25/30-F

	[V]	In [A]	Ian [mA]	Typ zabezpieczenia różnicowoprądowego		
KRD10-4/25/30-F	45776	400 AC	25	30	F	4
KRD10-4/32/30-F	45777	400 AC	32	30	F	4
KRD10-4/40/30-F	45778	400 AC	40	30	F	4
KRD10-4/63/30-F	45779	400 AC	63	30	F	4
KRD10-4/32/100-F	45780	400 AC	32	100	F	4
KRD10-4/63/100-F	45781	400 AC	63	100	F	4
KRD10-4/40/300-F	45782	400 AC	40	300	F	4
KRD10-4/63/300-F	45783	400 AC	63	300	F	4

Wyłącznik różnicowoprądowy typu F to nowocześniejsza wersja, zaprojektowana do instalacji z elektroniką i falownikami jednofazowymi. Typ F reaguje na więcej rodzajów prądu upływu, niż klasyczny typ AC, czy A:

AC – prąd przemienny sinusoidalny

A – AC + pulsujący DC

F – wszystko powyżej + prądy o mieszanych częstotliwościach (do ok.1 kHz) oraz krótkotrwałe składowe DC do 10mA.

Wyłącznik różnicowo-prądowy, 4P



KRD10-4/25/30-F



KRD10-4/32/30-F



KRD10-4/40/30-F



KRD10-4/63/30-F



KRD10-4/32/100-F




KRD10-4/63/100-F




KRD10-4/40/300-F




KRD10-4/63/300-F




KRD10-4/25/30-F



KRD10-4/32/30-F




KRD10-4/40/30-F




KRD10-4/63/30-F


Wyłącznik różnicowo-prądowy, 4P




KRD10-4/32/100-F



KRD10-4/63/100-F



KRD10-4/40/300-F



KRD10-4/63/300-F