

Kanlux

Kanlux FOGLER E

PIR
MOTION
sensor

HIGH
lumen



[V] 220-240 AC	[Hz] 50	[°] 120	≥20000	[h] 25000	ellipse ≤ 6x Machdam	Ra 80
	SMD			IP 20		
	[mm²] 1-1,5	[m] 6	[°] 360	[s] - [min] 2-2	[lx] 15-2000	0,5m



FOGLER E 12W NW

		[W]	[lm]	Tc [K]		SENSOR
FOGLER E 12W NW	18122	12	1000	4000	alb	PIR
FOGLER E 17W NW	18123	17	1100	4000	alb	PIR
FOGLER E 24W NW	18124	24	1800	4000	alb	PIR




FOGLER E 12W NW




FOGLER E 17W NW




FOGLER E 24W NW



FOGLER E 12W NW



FOGLER E 17W NW



FOGLER E 24W NW

Date of issue: 28.11.2025, 10:45

Ne rezervăm dreptul de a face modificări tehnice. Datele conținute în acest material nu sunt obligatorii din punct de vedere juridic.

Fotometrie: rezultatele obținute în timpul testării unui exemplar concret.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com