

Kanlux

Kanlux CTRL 12/24V RGBW CCT



CTRL 12/24V RGBW CCT



CTRL 12/24V RGBW CCT	22148	alb	12 DC; 24 DC	max 10	max 30	
REMOTE RGBW	22146	alb	2 x 1,5 DC		2 x AAA max 30	4
REMOTE 4 RGBW/CCT-B	22135	negru	2 x 1,5 DC		2 x AAA max 30	4
REMOTE N 8 RGBW/CCT-W	22134	alb	2 x 1,5 DC		2 x AAA max 30	8



CTRL 12/24V RGBW CCT




REMOTE RGBW




REMOTE 4 RGBW/CCT-B




REMOTE N 8 RGBW/CCT-W



CTRL 12/24V RGBW CCT



REMOTE RGBW



REMOTE 4 RGBW/CCT-B



REMOTE N 8 RGBW/CCT-W

Date of issue: 10.02.2026, 09:00

Ne rezervăm dreptul de a face modificări tehnice. Datele conținute în acest material nu sunt obligatorii din punct de vedere juridic.

Fotometrie: rezultatele obținute în timpul testării unui exemplar concret.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

RO