

## FUTURIO LED 55W 1480mm

Corp de iluminat LED rezistent la praf



[V] 220-240 AC	[Hz] 50	≥30000	50000	ellipse ≤3x MacAdam	Ra 80	SMD
		IP 65			IK 08	
[mm] 1,5+2,5	0,5m					



### FT1500 55W-840-RYF

	[W]	Tc [K]	TYPE	[°]	[lm]	lm/W	[mm]	[°C]
FT1500 55W-840-RYF	<b>28659</b>	55	4000	grooved	X115/Y105	8150	148	1480 -25÷35
FT1500 55W-840-INT	<b>28661</b>	55	4000	prismatic, fascicul îngust	X70/Y95	7900	144	1480 -25÷35
FT1500 55W-840-ASY	<b>28662</b>	55	4000	prismatic, asimetric	X75/Y95	7900	144	1480 -25÷35
FT1500 55W-840-OPL	<b>28665</b>	55	4000	opalescent	X130/Y110	7500	136	1480 -25÷35

- Materialul carcasei: PC
- Materialul abajurului: PC



FT1500 55W-840-RYF



FT1500 55W-840-INT




FT1500 55W-840-ASY




FT1500 55W-840-OPL

## FUTURIO LED 55W 1480mm


Corp de iluminat LED rezistent la praf




FT1200 55W-840



FT1200 55W-840



FT1200 55W-840



FT1200 55W-840