

HIERRO

Corp de iluminat liniar LED










 [V] 220-240 AC	 [Hz] 50	 ≥ 30000	 [h] 50000	 + ellipse $\leq 6x$ MacAdam	 Ra 80	 SMD
		 IP 20		 [°C] 5÷25		
 [mm ²] 1,5÷2,5		 0,5m				



HR-ML-WW-W-PT

HIERRO

Corp de iluminat liniar LED

								
		[W]	Tc [K]	TYPE	[°]		[m]	[mm]
HR-ML-WW-W-PT	37026	18	3000	raster	X60/Y60	alb	2350	595
HR-MM-WW-W-PT	37027	23	3000	raster	X60/Y60	alb	2850	595
HR-MH-WW-W-PT	37028	28	3000	raster	X60/Y60	alb	3300	595
HR-ML-WW-B-PT	37034	18	3000	raster	X60/Y60	negru	2100	595
HR-MM-WW-B-PT	37035	23	3000	raster	X60/Y60	negru	2500	595
HR-MH-WW-B-PT	37036	28	3000	raster	X60/Y60	negru	2900	595
HR-ML-WN-W-PT	37042	18	3500	raster	X60/Y60	alb	2400	595
HR-MM-WN-W-PT	37043	23	3500	raster	X60/Y60	alb	2900	595
HR-MH-WN-W-PT	37044	28	3500	raster	X60/Y60	alb	3350	595
HR-ML-WN-B-PT	37050	18	3500	raster	X60/Y60	negru	2150	595
HR-MM-WN-B-PT	37051	23	3500	raster	X60/Y60	negru	2600	595
HR-MH-WN-B-PT	37052	28	3500	raster	X60/Y60	negru	3000	595
HR-ML-NW-W-PT	37058	18	4000	raster	X60/Y60	alb	2450	595
HR-MM-NW-W-PT	37059	23	4000	raster	X60/Y60	alb	3000	595
HR-MH-NW-W-PT	37060	28	4000	raster	X60/Y60	alb	3450	595
HR-ML-NW-B-PT	37066	18	4000	raster	X60/Y60	negru	2200	595
HR-MM-NW-B-PT	37067	23	4000	raster	X60/Y60	negru	2650	595
HR-MH-NW-B-PT	37068	28	4000	raster	X60/Y60	negru	3050	595

- Materialul carcasei: oțel, material din plastic
- Materialul abajurului: material din plastic



HIERRO

Corp de iluminat liniar LED



HR-ML-WW-W-PT



HR-MM-WW-W-PT



HR-MH-WW-W-PT



HR-ML-WW-B-PT



HR-MM-WW-B-PT



HR-MH-WW-B-PT



HR-ML-WN-W-PT



HR-MM-WN-W-PT



HR-MH-WN-W-PT



HR-ML-WN-B-PT



HR-MM-WN-B-PT



HR-MH-WN-B-PT



HR-ML-NW-W-PT



HR-MM-NW-W-PT



HR-MH-NW-W-PT



HR-ML-NW-B-PT

HIERRO


Corp de iluminat liniar LED



HR-MM-NW-B-PT



HR-MH-NW-B-PT



HR-M-PT

