

Kanlux



Kanlux ARVOS N



[V] 220-240 AC	[Hz] 50	[°] 120	[h] ≥15000	[h] 25000	ellipse ≤ 6x Mackdam	Ra 80
Hg no	SMD		DIMMING function		IP 20	
°C 5+25			0,5m	telecomandă cu infraroșu	[lm] Φuse 570	360° Φuse
[W] P _{ON} 4,4	[W] 45	CE	EAC	UK CA		



ARVOS N LED 37W CCT B




ARVOS N LED 37W CCT B	37329	max 37	max 2680 (4000K)	3000-6500	negru
ARVOS N LED 37W CCT W	37332	max 37	max 2680 (4000K)	3000-6500	alb




ARVOS N LED 37W CCT B



ARVOS N LED 37W CCT W



ARVOS N LED 37W CCT B



ARVOS N LED 37W CCT W

Date of issue: 10.10.2025, 15:20

Ne rezervăm dreptul de a face modificări tehnice. Datele conținute în acest material nu sunt obligatorii din punct de vedere juridic.

Fotometrie: rezultatele obținute în timpul testării unui exemplar concret.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com