

Kanlux



Kanlux BLINGO U SR

- Materialul panoului/cadrului: fier



low
UGR

120 $\frac{\text{lm}}{\text{W}}$

$[\text{V}]$ 220-240 AC	$[\text{Hz}]$ 50	 ≥ 50000	 50000	 ellipso $\leq 6x$ Nachdam	 Ra 90	 SMD
		IP 20		 $5 \div 25$		 $0,75-2,5$
$\text{d} \cdots \text{m}$ 0,5m	CE	EAC	UK CA			



BLINGO U 34W SR 60 NW



$\frac{\text{lm}}{\text{W}}$



UGR


BLINGO U 34W SR 60 NW	39172	34	4080	120	4000	90	alb	<19
BLINGO U 34W SR 120NW	39173	34	4080	120	4000	90	alb	<19




BLINGO U 34W SR 60 NW



BLINGO U 34W SR 120NW



BLINGO U 34W SR 60 NW



BLINGO U 34W SR 120NW

Date of issue: 10.09.2025, 09:40

Ne rezervăm dreptul de a face modificări tehnice. Datele conținute în acest material nu sunt obligatorii din punct de vedere juridic.

Fotometrie: rezultatele obținute în timpul testării unui exemplar concret.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com