

HB PRO STRONG

Светодиодный светильник high bay




up to
170 $\frac{\text{lm}}{\text{W}}$

IP 65

10K



$[\text{V}]$ 220-240 AC	$[\text{Hz}]$ 50	$[\text{°}]$ 90	≥ 25000	$[\text{h}]$ 50000	ellipse $\leq 6x \text{ MacAdam}$	Ra 80
SMD	1-10V	⏏	IP 65	⏏	$[\text{°C}]$ -30÷50	⏏
IK 08	⏏	$[\text{m}]$ 0,3	$[\text{mm}^2]$ 1	⏏ 1m	⏏	CE
EAC	UK CA	⏏				



HB PRO STRONG 150W-NW



	$[\text{W}]$	$[\text{lm}]$	$\text{Tc} [\text{K}]$	
HB PRO STRONG 150W-NW 27158	150 112,5 75	25500 19125 12750	4000	черный
HB PRO STRONG 200W-NW 27159	200 150 100	34000 25500 17000	4000	черный

- 5 лет Гарантии на условиях гарантийного заявления, доступного на веб-сайте
- Материал корпуса: сплав алюминия
- Материал защитного стекла: пластмасса

HB PRO STRONG


Светодиодный светильник high bay




HB PRO STRONG 150W-NW



HB PRO STRONG 200W-NW



HB PRO STRONG 150W-NW



HB PRO STRONG 200W-NW