

# KIENO DALI LED P1

Светодиодный офисный светильник скрытого монтажа



[V] 220-240 AC	[Hz] 50	[h] ≥30000	[h] 50000	[ellipse] ≤ 6x MacAdam	[Ra] 80	SMD
[DALI]	[IP] 20	[House]	[Temperature] 5-25	[Lightbulb]	[UK CA]	
[mm²] 0,5-2,5	[D---m] 0,5m	CE				



KND-S6D-NW-B-P1



KND-S6D-NW-B-P1	37482	20	2650	4000	soczewka	60	черный
KND-S6D-NW-W-P1	37470	20	3000	4000	soczewka	60	белый
KND-S6D-WW-B-P1	37476	20	2450	3000	soczewka	60	черный
KND-S6D-WW-W-P1	37464	20	2800	3000	soczewka	60	белый
KND-S9D-NW-B-P1	37485	20	2600	4000	soczewka	90	черный
KND-S9D-NW-W-P1	37473	20	2950	4000	soczewka	90	белый
KND-S9D-WW-B-P1	37479	20	2400	3000	soczewka	90	черный
KND-S9D-WW-W-P1	37467	20	2750	3000	soczewka	90	белый

- Материал корпуса: металл
- Материал плафона: пластмасса

# KIENO DALI LED P1


Светодиодный офисный светильник скрытого монтажа



KND B P1



KND W P1



KND P1

