

KIENO DALI LED P1

Светодиодный офисный светильник скрытого монтажа



[V] 220-240 AC	[Hz] 50	[s] ≥30000	[h] 50000	[+/-] ellipse ≤ 6x MacAdam	[Ra] 80	[SMD]
[DALI]	[\oplus]	[IP] 20	[House]	[Δ] 5-25	[Δ]	[Δ]
[mm ²] 0,5-2,5	[D---m] 0,5m	[CE]	[UK CA]			



KND-L6D-NW-B-P1

KND-L6D-NW-B-P1	37483	26	3600	4000	soczewka	60	черный
KND-L6D-NW-W-P1	37471	26	4100	4000	soczewka	60	белый
KND-L6D-WW-B-P1	37477	26	3350	3000	soczewka	60	черный
KND-L6D-WW-W-P1	37465	26	3850	3000	soczewka	60	белый
KND-L9D-NW-B-P1	37486	26	3550	4000	soczewka	90	черный
KND-L9D-NW-W-P1	37474	26	4050	4000	soczewka	90	белый
KND-L9D-WW-B-P1	37480	26	3350	3000	soczewka	90	черный
KND-L9D-WW-W-P1	37468	26	3800	3000	soczewka	90	белый

- Материал корпуса: металл
- Материал плафона: пластмасса

KIENO DALI LED P1


Светодиодный офисный светильник скрытого монтажа



KN-B-P1



KN-W-P1



KN-P1

