

SIGO LED

Svetelný zdroj LED



[V] 220-240 AC	[Hz] 50	SMD	360° Φ _{use}	ellipse ≤ 6x Macadam	Ra 80	≥15000
15000 [h]	Hg		CE	EAC	UK CA	



SIGO R39 LED E14



	P ON [W]	[lm] Φ _{use}	Tc [K]	[°]				
SIGO R39 LED E14-WW	22733	4	29	320	3000	120	E14	G
SIGO R39 LED E14-NW	22734	4	29	320	4000	120	E14	G
SIGO R50 LED E14-WW	22735	6	41	490	3000	120	E14	G
SIGO R50 LED E14-NW	22736	6	41	490	4000	120	E14	G
SIGO R63 LED E27-WW	22737	8	54	720	3000	120	E27	F
SIGO R63 LED E27-NW	22738	8	54	720	4000	120	E27	F

Kanlux SIGO LED nie je iba úspora energie, ale tiež životnosť 25-krát vyššia ako u tradičných reflektorových žiaroviek. Ich tvar aj rozmer pripomína štandardné reflektorové žiarovky, ktoré je ľahké vymeniť bez akýchkoľvek ďalších úprav.

- Materiál difúzora: plast

SIGO LED

Svetelný zdroj LED




SIGO R39 LED E14




SIGO R50 LED E14




SIGO R63 LED E27



SIGO R39 LED E14



SIGO R50 LED E14



SIGO R63 LED E27