

FUTURIO LED 28W 1180mm

Prachotesné LED svietidlo



[V] 220-240 AC	[Hz] 50	≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
		IP 65			IK 08	
[mm²] 1,5÷2,5	0,5m	CE	ERC	PZH	UK CA	



FT1200 28W-840-OPL

	[W]	Tc [K]	TYPE	[°]	[mm]	[m]	[mm]	[°C]	
FT1200 28W-840-OPL	28850	28	4000	opálový	X130/Y110	4100	146	1180	-25÷40
FT1200 28W-840-RYF	28851	28	4000	drážkovaný	X115/Y105	4500	161	1180	-25÷40
FT1200 28W-840-INT	28852	28	4000	prizmatický, s úzkym lúčom	X70/Y95	4300	154	1180	-25÷40
FT1200 28W-840-ASY	28853	28	4000	prizmatický, asymetrický	X75/Y95	4300	154	1180	-25÷40

- 5-ročná záruka podľa podmienok vyhlásenia o záruke, ktoré je dostupné na webovej stránke
- Certifikát PZH: Číslo BK/K/0163/01/2019, platný do 2024-08-07
- Materiál korpusu: PC
- Materiál difúzora: PC

FUTURIO LED 28W 1180mm

Prachotesné LED svietidlo



FT1200 28W-840-OPL




FT1200 28W-840-RYF



FT1200 28W-840-INT



FT1200 28W-840-ASY



FT1200 28W-840