



XLED A60M

Svetelný zdroj LED



XLED A60M 4,5W, XLED A60M 7W, XLED A60M 8W,
XLED A60M 10W



	P0N (W)	[W]	[lm] Φ _{use}	T _c [K]	[°]		(h)	Ei	
XLED A60 4,5W-WW-M	29607	4,5	40	470	2700	320	E27	15000	F
XLED A60 4,5W-NW-M	29608	4,5	40	470	4000	320	E27	15000	F
XLED A60 7W-WW-M	29609	7	60	810	2700	320	E27	15000	E
XLED A60 7W-NW-M	29610	7	60	810	4000	320	E27	15000	E
XLED A60 8W-WW-M	29612	8	75	1055	2700	320	E27	15000	E
XLED A60 8W-NW-M	29613	8	75	1055	4000	320	E27	15000	E
XLED A60 10W-WW-M	29615	10	99	1520	2700	320	E27	10000	D
XLED A60 10W-NW-M	29616	10	99	1520	4000	320	E27	10000	D

Kanlux XLED kombinuje najlepšie vlastnosti tradičných žiaroviek a moderných LED svetelných zdrojov. Matná banka v tvare tradičnej žiarovky a LED diód usporiadaných tak, aby sa svetlo šíriло všetkými smermi a uhol osvetlenia bol až 320 stupňov!


- Materiál difúzora: sklo

XLED A60M

Svetelný zdroj LED



XLED A60M 4,5W, XLED
A60M 7W, XLED A60M 8W,
XLED A60M 10W



XLED A60M 4,5W, XLED
A60M 7W, XLED A60M 8W,
XLED A60M 10W