

KMB6

Istič, 1P+N



| | | | | | | |
|---------------|---|-----|----------|----------------------------|------------|-------|
| [Hz] 50 | C | 1+N | IP 20 | [mm ²] 1÷25 | °C 5÷40 | TH 35 |
| Ui [V] 500 | | | | | | |



KMBN6-C6/1

| | Ui [V] | | In [A] |
|-------------|---------------------|---|--------|
| KMBN6-C6/1 | 32567 230 AC | 1 | 6 |
| KMBN6-C10/1 | 32568 230 AC | 1 | 10 |
| KMBN6-C16/1 | 32569 230 AC | 1 | 16 |
| KMBN6-C20/1 | 32570 230 AC | 1 | 20 |
| KMBN6-C25/1 | 32571 230 AC | 1 | 25 |
| KMBN6-C32/1 | 32572 230 AC | 1 | 32 |

Istič slúži na ochranu pred preťažením a skratom v inštaláciách a zariadeniach.



KMBN6-C6/1



KMBN6-C10/1



KMBN6-C16/1



KMBN6-C20/1

KMB6


Istič, 1P+N




KMBN6-C25/1




KMBN6-C32/1




KMBN6-C6/1




KMBN6-C10/1




KMBN6-C16/1



KMBN6-C20/1



KMBN6-C25/1



KMBN6-C32/1