

XLED A60 B22 M

Svetelný zdroj LED



[V] 220-240 AC	[Hz] 50	FILAMENT	360° Φ _{use}	ellipse ≤ 6x MacAdam	Ra 80	≥15000
		CE	EAC	UK CA		



XLED A60 B22 7W-WW-M



	P _{ON} [W]	[W]	[°]	[lm] Φ _{use}	Tc [K]	[h]	E _i A G
XLED A60 B22 7W-WW-M	33102	7	60	810	2700	320	B22 15000 E
XLED A60 B22 7W-CW-M	33103	7	60	810	6500	320	B22 15000 E
XLED A60 B22 10W-WW-M	33108	10	99	1520	2700	320	B22 10000 D
XLED A60 B22 10W-CW-M	33109	10	99	1520	6500	320	B22 10000 D

Kanlux XLED A60 B22 M spája tie najlepšie vlastnosti tradičných žiaroviek a moderných LED zdrojov svetla. Matná banka v tvare tradičnej žiarovky a LED diódy usporiadané tak, aby sa svetlo šírilo všetkými smermi a uhol svietenia bol až 320 stupňov! Žiarovky XLED A60 B22 M majú päťicu B22.


- Materiál difúzora: sklo

XLED A60 B22 M

Svetelný zdroj LED



XLED A60M B22 7W, 10W



XLED A60 B22