

iQ^{LED}

Kanlux

IQ-LED G45

Svetelný zdroj LED



[V] 220-240 AC	[Hz] 50	SMD	360° Φ _{use}	ellipse ≤ 6x MacAdam	Ra 80	≥40000
25000 [h]	Hg	CE	EAC	UK CA	RoHS	



IQ-LED G45E14 4,2W-NW



		Pon [W]	Φ [lm]	Tc [K]	τ [s]	Φ _{use}	Base	Beam
IQ-LED G45E14 4,2W-NW	33735	4,2	40	470	4000	240	E14	E
IQ-LED G45E14 7,2W-CW	33742	7,2	60	806	6500	240	E14	E
IQ-LED G45E27 7,2W-WW	33743	7,2	60	806	2700	240	E27	E

Kanlux IQ-LED znamená fotobiologickú bezpečnosť, šetrnú teplotu farieb očí a spoľahlivosť, to všetko v klasickom dizajne G45. Žiarovky Kanlux IQ-LED poskytujú plný komfort používania a bezpečnosť.

Vytvorený dokument: 29.09.2025, 15:40

Zmena technických parametrov vyhradená. Údaje, ktoré sú uvedené v tomto materiáli, nie sú právne záväzné.

Fotometria: výsledky získané pri testovaní konkrétneho exemplára.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

SK

iQ^{LED}

Kanlux

IQ-LED G45

Svetelný zdroj LED




IQ-LED G45E14 7,2W

iQ^{LED}

Kanlux

IQ-LED G45

Svetelný zdroj LED



IQ-LED G45E14 7,2W