

Kanlux



Kanlux ALIN IP55 LED



[V] 220-240 AC	[Hz] 50	≥ 30000	[h] 50000	ellipse $\leq 3 \times \text{MacAdam}$	Ra 80	SMD
		IP 55		[°C] -20÷35		
[mm°] 0,5÷1	[m] 0,5m	CE	EAC	UK CA		



AL55-SH-NW-MAT-W-NT



AL55-SH-NW-MAT-W-NT	38860	18,9545	2500	4000	matné	X85/Y95	biela
AL55-SH-WW-MAT-W-NT	38970	18,9545	2400	3000	matné	X85/Y95	biela
AL55-SH-NW-MAT-B-NT	38973	18,9545	2500	4000	matné	X85/Y95	čierna
AL55-SH-WW-MAT-B-NT	38976	18,9545	2400	3000	matné	X85/Y95	čierna



AL55-SH-NW-MAT-W-NT




AL55-SH-WW-MAT-W-NT



AL55-SH-NW-MAT-B-NT



AL55-SH-WW-MAT-B-NT



Vytvorený dokument: 01.10.2025, 14:20

Zmena technických parametrov vyhradená. Údaje, ktoré sú uvedené v tomto materiáli, nie sú právne záväzné.

Fotometria: výsledky získané pri testovaní konkrétneho exemplára.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

