

Kanlux

Kanlux ALIN IP55 LED



[V] 220-240 AC	[Hz] 50	[h] ≥30000	[h] 50000	ellipse ≤3x MacAdam	Ra 80	SMD
IP 55	[°C] -20÷35	CE	EAC	UK CA		
[mm²] 0,5÷1	[m] 0,5m					



AL55-SL-NW-MAT-W-NT



		[V]	[lm]	Tc [K]	TYPE	[°]	
AL55-SL-NW-MAT-W-NT	38979	9,1935	1300	4000	matné	X85/Y95	biela
AL55-SL-WW-MAT-W-NT	38982	9,1935	1200	3000	matné	X85/Y95	biela
AL55-SL-NW-MAT-B-NT	38985	9,1935	1300	4000	matné	X85/Y95	čierna
AL55-SL-WW-MAT-B-NT	38988	9,1935	1300	3000	matné	X85/Y95	čierna



AL55-SL-NW-MAT-W-NT




AL55-SL-WW-MAT-W-NT



AL55-SL-NW-MAT-B-NT



AL55-SL-WW-MAT-B-NT



Vytvorený dokument: 01.10.2025, 14:20

Zmena technických parametrov vyhradená. Údaje, ktoré sú uvedené v tomto materiáli, nie sú právne záväzné.

Fotometria: výsledky získané pri testovaní konkrétneho exemplára.

Kanlux S.A. ul. Objazdowa 1-3, 41-922 Radzionków, Poland kanlux@kanlux.com

